
SupIR 75mm f/1.2, Manual Focus 680189







HFOV	320x240	384x288	640x480	1024x768
15µ	3.7°	4.4°	7.3°	
10µ	2.4°	2.9°	4.9°	7.8°
5μ			2.4°	3.9°

Property			Value					
Optical								
Focal Length			75mm					
F#			1.2					
Average transmission (3.4-5µm)			95% (HD)					
Back Focal Length			44.05mm	44.05mm in air				
Mechanical								
Focus Mechanism			Manual					
Depth of Field			400m to ir	400m to infinity				
Focus Range			5m to infin	5m to infinity				
Weight			782gr	782gr				
Max. Dimensions			Ø107.6mr	Ø107.6mm x 87.9mm				
Environmental								
Operation Temperature			-20°C to +55°C					
Storage Temperature			-40°C to +80°C					
Sealing			IP 65 front	IP 65 front element only				
Configurations	Weight (gr)	Dimensions	BWD**	Thread	Coating			
680189-001	782	Ø107.6mm X 87.9mm	32.4	Bayonet	HD			

^{**} The BWD value is calculated for a unique detector setup with varying sealing windows in terms of thickness and material. For more details, contact your local sales representative.



^{*} The ICD drawing provided here is primarily a representation and may not accurately reflect the product's actual dimensions and specifications. For precise integration specifications contact your local sales representative.